

Elite Prime Vision Motor Specifications Table (110V)

Motor Model (Type)	Products used in	Motor Diag. (cm/inch)	Torque	RPM	Db	Output Torque	Output Current	Voltage	Power	Frequency	Tube Diameter	Running Time	Tube Length	Insulation Class	Protection Index
ES35-6-14 (Tubular)	PowerMax Pro2 Series, PowerMax Sonic Series	3.5/1.38	6Kg/cm	14	48db	6Nm	0.77A	AC110V	85 watts	60Hz	35mm	4 min.	405 mm	F	IP44
ES35-3-28 (Tubular)	PowerMax Series 84"(included) - 110"(included)	3.5/1.38	3Kg/cm	28	48db	3Nm	0.77A	AC110V	85 watts	60Hz	35mm	4 min.	405 mm	F	IP44
ES45-10-17 (Tubular)	Merlin Pro Series	4.5/1.78	10Kg/cm	17	48db	10Nm	1.18A	110V	130 watts	60Hz	45mm	5 min.	500mm	F	IP44
ES45-8-30 (Tubular)	Peregrine Twin Series 117" and below, Peregrine Tension Series 120"(included)-92" 16:9 (included), Aerie Tab-Tension In-Ceiling Screen, PowerMax Tab-Tension Series	4.5/1.78	8Kg/cm	30	48db	8Nm	1.18A	110V	130 watts	60Hz	45mm	5 min.	500mm	F	IP44
ES45-15-30 (Tubular)	Peregrine Twin Series 120" and above, Peregrine Tension 120"above	4.5/1.78	15Kg/cm	30	48db	15Nm	1.64A	110V	180 watts	60Hz	45mm	5min.	600mm	F	IP44
Synchronous Motor B	EPVMax	6.0/2.36	17Kg/cm	16	46db	17Nm	1.90A	110V	38 watts	60Hz	N/A	N/A	N/A	E	N/A

Elite Prime Vision Motor Specifications Table (220V)

Motor Model (Type)	Products used in	Motor Diag. (cm/inch)	Torque	RPM	Db Level	Output Torque	Output Current	Voltage	Power	Frequency	Tube Diameter	Running Time	Tube Length	Insulation Class	Protection Index
ES35-6-14 (Tubular)	PowerMax Pro2 Series, PowerMax Sonic Series	3.5/1.38	6	14	48db	6Nm	0.43 A	AC220V	95 watts	50Hz	35 mm	4 min.	405 mm	F	IP44
ES35-3-28 (Tubular)	PowerMax Series 84"(included) - 110"(included)	3.5/1.38	3	28	48db	3Nm	0.43A	AC220V	95 watts	50Hz	35mm	4 min.	405 mm	F	IP44
ES45-10-17 (Tubular)	Merlin Pro Series	4.5/1.78	10	17	48db	10Nm	0.64A	220V	140 watt	50Hz	45mm	5 min.	500mm	F	IP44
ES45-8-30 (Tubular)	Peregrine Twin Series 117" and below, Peregrine Tension Series 120"(included)-92" 16:9 (included), Aerie Tab-Tension In-Ceiling Screen, PowerMax Tab-Tension Series	4.5/1.78	8	30	48db	8Nm	0.64A	220V	140 watt	50Hz	45mm	5 min.	500mm	F	IP44
ES45-15-30 (Tubular)	Peregrine Twin Series 120" and above, Peregrine Tension 120"above	4.5/1.78	15	30	48db	15Nm	0.86A	220V	190 watt	50Hz	45mm	5 min.	600mm	F	IP44
Synchronous Motor B	EPVMax	6.0/2.36	17Kg/cm	16	46db	17Nm	1.90A	220V	38 watts	50Hz	N/A	N/A	N/A	E	N/A